



Super Bond Activset

A fine mist spray for use with any Super Bond adhesive for increased bond strength and accelerated cure



Features & Benefits

- Primer and accelerator in one - for improved bond strength, even on hard-to-bond materials, and for accelerated cure
- Fine mist spray - for a homogeneous application
- Non blooming - for a perfect finish on visible repairs

P/N	Product	S/C	Packaging
86629	Super Bond Activset	KSBA	150 ml aerosol

Application

Super Bond Activset can be used to enhance bond strength and cure speeds, on porous and acidic surfaces, as well as on hard-to-bond materials, like EPDM, polyethylene, polypropylene and glass.

Super Bond Activset is also very useful to cure the exposed uncured Super Bond adhesive after gap filling operations.

Super Bond Activset is ideal for use in not optimal external conditions for cyanoacrylate adhesives, e.g. dry and/or cold environments.

Super Bond Activset can be used in combination with any KENT Super Bond adhesive.

Instructions

1. Before use, a compatibility test should be performed on a hidden place of the surface.
2. For best results, surfaces to be bonded must be clean, free from dirt, waxes, oils, etc. using KENT Acrysol or Soft Surface Cleaner.
3. Protect your hands using KENT Super Bond Protect, to avoid fingers to stick together.
4. Apply Super Bond Activset to one surface and Super Bond adhesive to the other surface, respecting a spraying distance of 20 to 30 cm, and allow flashing off.
5. Bring the surfaces together immediately, taking care to ensure the correct alignment.
6. Apply firm pressure to ensure that the adhesive spreads into a thin film.
7. Do not disturb or re-align until the curing is achieved.
8. For gap filling repairs, apply Super Bond Activset on the exposed uncured Super Bond adhesive and allow to cure.
9. Any surplus liquid adhesive may be removed with KENT Super Bond Remover.
10. Always close cap of the adhesive after use, ensuring it is correctly secured, and wipe the tip clean.



Technical Information

Base:	Acetone
Consistency:	Liquid
Colour:	Clear
Shelf life:	24 months
Custom tariff code:	3814 00 0000
VOC:	702 g/l



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd., or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30
Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: kentinfo.uk@kenteurope.com

Rev: 05.04.2019