



Rotabond FAST Tack

Extremely fast one-component MS-Polymer adhesive with high tack performances.



Features & Benefits

- Extremely fast initial grab - Holds heavy loads instantly
- Very good green strength - High initial grab
- Primerless - Cost efficient
- Easy to apply with hand gun - No expensive dispensing equipment needed
- No solvents or isocyanates - Completely safe to use
- Heavy bodied adhesive - No slump or sag
- Does not string - Neat application and quality finish

P/N	Product	S/C	Packaging
86608	Rotabond FAST Tack	RBFT	290 ml cartridge

Application

Rotabond FAST Tack is for use as an adhesive with exceptionally fast initial grab. Adheres to primed, painted and bare metal, zinc coating, aluminum, wood, concrete, ceramic, brick, stone, plaster, glass, fibreglass and PVC.

Rotabond FAST Tack can be used for fixing of all horizontal and vertical supports, indoor and outdoor. Fixing of panels, insulation plates, plaster panels, heavy MDF, signposting, frames, glazing, mirrors, tiling (large areas), etc.

Rotabond FAST Tack does not tolerate high thermal expansion or large movements of the bonded substrates. For this purpose, prefer Rotabond Hi Tack.

Instructions

1. Ensure surface is clean using KENT Soft Surface Cleaner and allow to dry.
2. Apply Rotabond FAST Tack as required, in a way that air can always circulate along the sides of the bead.
3. Assemble the parts within 5 minutes.

N.B Etch primers must not be applied OVER the top of this product.



Technical Information

General info

Base material:	MS Polymer
Consistency:	Smooth paste
Colour:	White
Shelf Life:	12 months
Customs Tariff Code:	32141010
VOC:	0 g/l
Hazard info:	None

Cure mechanism:	Moisture cure	Green strength:	1250 Pa (Physical rheometer MC100)
Density:	1.4 g/ml	Tensile strength (100 %):	3.3 MPa (DIN 53504/ISO 37)
Skin forming time:	5 min (20° C/50% RH)	Elongation at break:	190 % (DIN 53504/ISO 37)
Open time:	<10 min (20° C/50%RH)	Shear strength:	4.0 MPa (DIN 53283/ASTM D1002)
Cure speed @ 24 hrs:	2 mm (20° C/50%RH)	E-modulus (10 %):	8.2 MPa (DIN 53504/ISO 37)
Hardness:	Shore A 68 (DIN 53505)	Gap fill:	Min. 2 mm / Max. 2 cm
Volume change:	<3% (DIN 52451)	Salt water resistance:	Very good
Application temp:	+5° C to +35° C		
Temp resistance :	-40° C to +110° C		



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd., or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Way, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenturope.com

REV: 11.03.2018