



# HST Clear

A reinforced acrylic foam tape providing a superior bond to most plastics and metals.



HST clear	85380 – 6mm x 5m
HST clear	85381 – 12mm x 5m
HST clear	85604 - 19MM X 5M
HST clear	85605 - 25MM X 5M
HST clear	85606- 12MM X 10M

## Features

- Acrylic based
- Completely transparent
- Superb bonding characteristics
- UV resistant

## Applications

Excellent adhesion to wide range of substrates, including glass, metal, ceramic surfaces. HST Clear is extremely resistant to solvents, chemicals, UV and heat.

### Applications include:-

Bumper inserts, plastic side mouldings to vehicles, workshop signs, side-skirts and spoiler kits, Perspex covers, head, tail and side light lenses, sun roof trims and rubbers, any invisible repairs

## Benefits

- Can be used with high plasticiser migration plastics
- Excellent for cosmetic fixtures and repairs
- Consistent long lasting bond
- Excellent weathering properties

## Instructions

All surfaces to be sealed or bonded must be clean and dry and free from contaminants.

Care must be taken to ensure that plastic moulded components are free from release agents.

Press firmly into position to achieve maximum benefit from pressure sensitive adhesive.



## Technical Information

<b>Description:</b>	HST clear tape	<b>Peel Adhesion:</b>	PSTC-3 2.8kgs/25mm
<b>Shelf life:</b>	12 mths from manufacturing	<b>Shear Adhesion:</b>	PSTC-7 over 72 hrs, with
<b>Selling Unit:</b>	EA		2kg on 25mm x 25mm at 25°C
<b>Custom tariff code:</b>	3919 10 39	<b>Tensile strength</b>	Over 50kgs/25mm x 25mm
<b>SDS:</b>	yes	<b>Heat Resistance:</b>	PSTC-9 over 24 hrs, 1kg on
<b>Adhesive:</b>	High tack acrylic		25mm x 25mm at 80°C
<b>Carrier:</b>	Clear acrylic foam base	<b>Service temp;</b>	-40 to 170°C
<b>Thickness:</b>	1mm	<b>Application temp:</b>	-10 to 150°C
<b>Liner:</b>	Red HDPE tape		

(PSTC = Pressure Sensitive Tape Council)



SDS available on [www.kenturope.com](http://www.kenturope.com)

### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

**Registered Office:** Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ  
All rights reserved.

**KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US**  
**Tel :** 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.  
For out of hours queries please **Fax** us on 01383 735829 or **Email:** [kentinfo.uk@kenturope.com](mailto:kentinfo.uk@kenturope.com)

Rev: 05/04/2017