



Versatape

Versa tape is a self adhesive sealing and fixing tape with permanent plasticity based on synthetic rubber; for sealing joints that do not bear mechanical forces.



Part N°:
34830: 12.5mm
34835: 19mm

Features

- Permanent plastic / no shrinkage
- No solvents/flammable vapours
- Economical – saves time
- Available in 2 sizes

Applications

- Suitable for interior and exterior application:
- Sealing of lap joints (mechanically affixed)
 - Bonding foil and light weight materials
 - Vibration and sound insulation
 - Corrosion protection in metal joints especially between dissimilar materials to avoid contact corrosion.
 - Adheres - side moulding
 - impacts and rub strips
 - emblems
 - carpets
 - trunk mats
 - Seals
 - halo frames of sunroofs
 - fenders at mounting flange
 - Sound deadener for door skins, body panels

Benefits

- Provides vibration and sound insulation
- Safe for user
- No mixing time, no waiting for tack to develop
- A size to fit many applications

Instructions

The surfaces to be bonded must be dry and clean of dust, grease, or oil.
Cut the tape according to the required length and handle them with the support foil to avoid stretching or deforming.

The tape is applied to one side of the joint, the cover foil is removed and the counter part pressed on to the sealing strip.

To avoid deformation, place the spools horizontally in the original packaging. Protect against dust and mechanical loads.



Technical Information

Part number:	34830 / 34835	Ageing resistance: good, especially in warm / humid conditions
Description:	34830: Versa tape 12.5mm 34835: Versa tape 19mm	Chemical resistance: Resistant to water and sea water in the range of pH 5 (slightly acidic) to pH 10 (slightly alkaline). Not resistant to concentrated acidic or caustic solutions or oil, grease, petrol or other solvents.
Part code:	34830: VTB12 34835: VTB19	
Shelf life:	36 months	
Colour:	Black	
Thickness:	2.0mm	
Length:	15 meters	Service temperature: -30°C to 90°C
Replacing:	N/A	Application Temperature: 5°C to 35°C
Customs Tariff code:	3919101	
SDS:	Yes	



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 17/3/2017