

Plaz Tex Black

Allows the replication of the molded texturising on modern plastic bumpers, dashboards and other plastic fittings.



Features

- · Coarse textured paint
- Suitable for most plastics
- Fast drying
- No wastage
- Excellent coverage with each coat
- Compatible with leading paint systems

Benefits

- Matches many OEM finishes
- Use with confidence
- Allows quick throughput
- Saves money
- Saves time
- No comebacks

Part No.	Description	Packagin
86235	400ml	Aerosol

Application

Plaz Tex Black is designed for retexturing plastics after a plastic repair has been undertaken. It can be used for cosmetic repairs on: Bumpers, spoilers, air dams, side skirts, mirror housings and plastic wheel trims, Holes in dashboards, centre consoles, plastic door panels and fascia trim.

Typical customers who will find a use for this product will include: -

- Existing Plastic Repair customers
- · Body shops
- SMART Repair specialists
- · Used vehicle preparation sites
- Fleet repair specialists

Instructions

Application/results are dependent on the skill of the user and this is only achieved with practice.

- 1. Shake the can thoroughly before using.
- Thoroughly clean the area to be painted. Allow to dry.
- 3. If necessary, mask off area to be sprayed.
- 4. Spray light coats from a distance of 50-55 cm (this is vital).
- 5. Allow minimum of 5 minutes between coats.
- 6. Repeat steps 3-4 until desired finish is achieved.
- 7. It will be necessary to blend/feather the edges of the repair with the natural texture of the plastic.
- 8. Turn can upside down and spray after use to prevent clogging



Technical Information

Part No: 86235 Skin drying time: ~ 5 minutes

Description: Plax Tex Black Wet on Wet: No

Shelf Life: 24 months Coarse spray nozzle:86263 00 (pack of 6 pcs)

Selling Unit: EA

Hazard info: Harmful & Extremely Flammable

VOC: 575g/l **Stock Code:** PTC

Customs Tariff Code:3208 20 10

VOC Markings: 2004/42/IIB(e)(840/575



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US Tel: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.

For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenteurope.com

Rev: 2/3/2017