



Plaz Tex Clear 2

Allows the replication of the molded texturing on modern plastic bumpers, dashboards and other plastic fittings.



Part N^o: 84586 Plaz Tex Clear 2 (PTC2) 400ml Aerosol

Features

- Recreates OEM Finish
- Fast drying
- Suitable for most plastics
- Compatible with leading paint systems

Benefits

- Gives undetectable repair
- Quick throughput in workshop
- Use with confidence
- No comebacks

Applications

Plaz Tex Clear 2 is the ideal solution to re-texturing plastics after a plastic repair has been undertaken. It can be used for cosmetic repairs on: -

Bumpers, spoilers, air dams, side skirts, mirror housings and plastic wheel trims, Holes in dashboards, centre consoles, plastic door panels and fascia trim.

Typical applications include: -

- Existing Plastic Repair
- Bodyshops
- SMART Repair specialists
- Used vehicle preparation sites
- Fleet repair specialists

Instructions

Key area requiring texturing with light abrasive or Nylon finishing pads.

De-grease with suitable cleaner such as KENT Plastic Prep or Acrysol.

Allow to dry thoroughly

Mask off area to be re-textured.

Shake aerosol can thoroughly before use

Spray light coats of Plaz Tex Clear 2 to repair surface from a distance of 20-30cm in short, sweeping bursts. Allow a minimum of 5 minutes between coats. Repeat steps 2/3 until desired finish is achieved.

It will be necessary to feather (blend) in the edge of the re-textured area with the natural texture of the bumper.

NB. Invert can and spray out to avoid blockage of the nozzle.



Technical Information

Unit of sale:	each	Product colour:	Clear
Operating Temperature range:	-40 to +80C	Consistency:	Liquid
Packaging:	Aerosol	Odour:	Solvent
Size:	400ml	Storage Life:	120 months
		Tariff Code:	3208 90 19
		VOC:	672 g/l

VOC Markings : 2004/42/IIB(e)(840)672



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 06/04/2017